





PACKAGE HEAT PUMP

MPH*1M414A



- ✓ Easy Installation & Service
- ✓ Superior Performance
- ✓ Durable Build & Finish
- ✓ Antimicrobial Drain Pan
- ✓ R-410A Refrigerant

- ✓ Optional Electric Heat
- Louvered Coil Guard
- ✓ Compact Design



Sensible heating and cooling solutions with our affordable and durable packaged heat pump options.

48 Remington Way Hickory, KY 42051 270.366.0457

www.mrcool.com Version Date: 01-19-2023



‡Warranty provides for a total of 10 years of limited warranty coverage (Standard 5-year limited parts warranty plus an additional 5-year limited extended parts warranty; 15-year for heat exchanger where specified). Warranty must be registered online within 60 days of installation to qualify for extended coverage. Unregistered equipment defaults to 5-year coverage.

UP TO 13.4 SEER2 / 6.7 HSPF2

PACKAGE HEAT PUMP

MPH*1M414A

A MRCOOL® packaged heat pump combines highperformance cooling and powerful heating in one convenient, easy-to-install system. These units are competitively priced and operate at 14 SEER efficiency. A MRCOOL® packaged heat pump will be a great solution for tough air comfort problems in a suburban home, commercial office space, condominium, seaside villa, or wherever else you desire.

- Available in 2, 2.5, 3, 3.5, 4, and 5 ton capacities.
- 10-Year Parts Limited Warranty.:

SPECIFICATIONS

| MODEL NO. | Unit | MPH241M414A | MPH301M414A | MPH361M414A | MPH421M414A | MPH481M414A | MPH601M414A |
|--------------------------------|----------|-----------------------|-----------------------|-----------------------|-----------------------|-----------------------|-----------------------|
| Power Supply | V~Hz, Ph | 208/230 ~ 60, 1 | 208/230 ~ 60, 1 | 208/230 ~ 60, 1 | 208/230 ~ 60, 1 | 208/230 ~ 60, 1 | 208/230 ~ 60, 1 |
| Cooling Capacity | Btu/h | 23000 | 28600 | 34000 | 39500 | 45500 | 56000 |
| SEER2 | Btu/w | 13.4 | 13.4 | 13.4 | 13.4 | 13.4 | 13.4 |
| EER2 | Btu/w | 10.6 | 10.6 | 10.6 | 10.6 | 10.6 | 10.6 |
| Heating Capacity | Btu/h | 21600 | 25800 | 32600 | 40000 | 47000 | 58000 |
| HSPF2 | Btu/w | 6.7 | 6.7 | 6.7 | 6.7 | 6.7 | 6.7 |
| Outdoor Unit Dimension (WxDxH) | inch | 47.66 x 47.66 x 40.89 | 47.66 x 47.66 x 40.89 | 47.66 x 47.66 x 40.89 | 56.13 x 47.66 x 44.89 | 56.13 x 47.66 x 44.89 | 56.13 x 47.66 x 44.89 |
| Outdoor Unit Packaging (WxDxH) | inch | 48.75 x 48 x 42.5 | 48.75 x 48 x 42.5 | 48.75 x 48 x 42.5 | 57.25 x 48 x 48 | 57.25 x 48 x 48 | 57.25 x 48 x 48 |
| Sound Rating (Hi/Mi/Lo) | dB(A) | 78 | 78 | 78 | 78 | 79 | 78 |
| Weight | lbs | 369 | 379 | 388 | 460 | 464 | 503 |
| Refrigerant Type | Туре | R-410A | R-410A | R-410A | R-410A | R-410A | R-410A |
| Refrigerant Charge | lb-oz | 86 | 91 | 91 | 167 | 173 | 174 |







^{*}Data provided by AHRI