MRCOOL

Packaged Terminal

Air Conditioner/Heat Pump

Eco-Friendly & Quiet Operation

AHRI Listed

ETL Certification

Fresh Air Filter

Auto Restart Function

Heat Kit Included

R-410A Eco-Friendly Refrigerant

2 Year Limited Warranty

*Truckload orders only

Quiet Running

R410A Refrigerant

Electric Heat Included

Fresh Air Filter

Auto Restart Function

MRCOOL™ COMFORT MADE SIMPLE

SPECIFICATION

MODEL NO.		UNITS	PTAC07325	PTAC09335	PTAC12335	PTAC15335
Cooling Capacity		Btu/h	7300-7100	9200-9000	12000-11800	14700-14500
EER		Btu/W*h	11.9	11.3	10.7	9.5
Heating Capacity		Btu/h	--	--	--	--
COP			--	--	--	--
Noise (Sound Pressure) Level	Indoor	dB(A)	50/48/46	50/48/46	52/49/46	53/50/45
	Outdoor	dB(A)	61	63	66	66
Supplemental Electric Heat		kW	2.5	3.5	3.5	3.5
Power supply		Ph-V-Hz	1 - 208/230 - 60	1 - 208/230 - 60	1 - 208/230 - 60	1 - 208/230 - 60
Minimum Circuit Ampacity		A	14	20	20	20
Connection wiring		AWG	14AWG x 3	12AWG x 3	12AWG x 3	12AWGx3
Cooling Current Rating		A	3.91	5.9	8.7	10.6
Heating Current Rating		A	--	--	--	--
Starting Current Rating		A	16	18	25.9	39
Dimension (WxDxH)	Net	inch	42 x 21 x 16	42 x 21 x 16	42 x 21 x 16	42 x 21 x 16
	Packing	inch	45 x 25.4 x19.3	45 x 25.4 x 19.3	45 x 25.4 x 19.3	45 x 25.4 x 18.7
Weight	Net	lbs	99.2	104.7	115.7	117.9
	Gross	lbs	130	130	145	150
Refrigerant Type		--	R410A	R410A	R410A	R410A
Refrigerant Charge		oz	24.69	24.69	31.39	37.04
Cooling Operation Range	Indoor	° F	62-90	62-90	62-90	62-90
	Outdoor	° F	64-109	64-109	64-109	64-109
Heating Operation Range	Indoor	° F	32-80	32-80	32-80	32-80
	Outdoor	° F	23-76	23-76	23-76	23-76

SPECIFICATION

MODEL NO.		UNITS	PTHP07325	PTHP09335	PTHP12335	PTHP15335
Cooling Capacity		Btu/h	7200 - 6800	9000 - 8800	10800 - 10500	13500 - 13200
EER		Btu/W*h	11.9	11.3	10.5	9.6
Heating Capacity		Btu/h	6000 - 5800	8100 - 7900	10800 - 10500	13500 - 13200
COP			3.4	3.4	3.2	3.0
Noise (Sound Pressure) Level	Indoor	dB(A)	50/48/46	50/48/46	53/50/45	53/50/45
	Outdoor	dB(A)	61	61	66	66
Supplemental Electric Heat		kW	2.5	3.5	3.5	3.5
Power supply		Ph-V-Hz	1 - 208/230 - 60	1 - 208/230 - 60	1 - 208/230 - 60	1 - 208/230 - 60
Minimum Circuit Ampacity		A	14	20	20	20
Connection wiring		AWG	14AWG x 3	12AWG x 3	12AWG x 3	12AWG x 3
Cooling Current Rating		A	2.65/2.76	3.46/3.75	4.97/5.4	6.66/7.26
Heating Current Rating		A	2.25/2.41	3.04/3.28	4.3/4.63	5.74/6.2
Starting Current Rating		A	16	18	25.9	39
Dimension (WxDxH)	Net	inch	42 x 21 x 16	42 x 21 x 16	42 x 21 x 16	42 x 21 x 16
	Packing	inch	45 x 25.4 x 19.3	45 x 25.4 x 19.3	45 x 25.4 x 19.3	45 x 25.4 x 18.7
Weight	Net	lbs	101.4	106.9	117.9	120
	Gross	lbs	130	130	145	150
Refrigerant Type		--	R410A	R410A	R410A	R410A
Refrigerant Charge		oz	24.69	24.69	31.39	37.04
Cooling Operation Range	Indoor	° F	62-90	62-90	62-90	62-90
	Outdoor	° F	64-109	64-109	64-109	64-109
Heating Operation Range	Indoor	° F	32-80	32-80	32-80	32-80
	Outdoor	° F	23-76	23-76	23-76	23-76